

FB 3150 Threaded protectiontube according to DIN 43772 Form 2G, 3G

Fabricated tube well

Design	2G or 3G to DIN 43772
Process connection	Welded Male threaded
Material	SS 316 - (Wst 1.4401)

Instrument connection

Free moving nut	Male M24x1.5mm standard
Welded nut	Optional: Female nut 1/2

Stem /Shrank

Insertion length	To specify
DIN43772 Form 2G	Straight over full length
DIN43772 Form 3G	Tip tapered over 50 mm to dia. 9.0 mm
Inside diameter	To suit 6.0mm or 8.0mm sensors

Process connection

Process connection	1/2
Lagging	To specify
	Other materials: Monel400, Hasteloy C276 or C4, Titanium Gr.II

Options

Other dimensions
Tantalum protective jacket

Tube size	Sensor	Form
9 x 1 mm	6.0mm	2G or 3G
11 x 2 mm	6.0mm	2G or 3G
12 x 2.5 mm	6.0mm	2G or 3G
14 x 2.5 mm	8.0mm	2G or 3G
15 x 3 mm	8.0mm	2G or 3G

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	FB 3150				
Length "U" in mm					
Length "X" in mm					
Form 2G or 3G					
Tube size					



H3-1 Rev. 07/07